

Microplotter[®] Proto

Benchtop picoliter printing



Key Features

- Noncontact deposition
- Features as small as 30 μm
- Viscosities up to 450 cP
- True contiguous lines, arcs, and bends
- Consistent spot size & shape with coefficients of variability of 10%
- 3-axis positioning with 20 μm resolution
- Integrated digital video capture
- Automated surface calibration
- Interchangeable holding platen for a variety of substrate sizes
- SonoGuide™ software for full automation and control
- SonoDraw™ software as a CAD layout tool

Applications

- Rapid prototyping
- Macroelectronic printing
- MEMS printing
- Protein microarrays
- MALDI-ToF spotting
- Patterning of live cells

For More Information

Visit www.sonoplot.com
 Email sales@sonoplot.com
 Call +1 608.824.9311

The SonoPlot Microplotter[®] Proto is a benchtop picoliter fluid dispensing system for the microarray and printed electronics markets with significant advantages over existing products in deposited feature size and type, regularity of volumes dispensed, and flexibility for the user.

The core of the Microplotter[®] technology is a dispenser that uses controlled ultrasonics to deposit fluid in a non-contact manner. This patented technology can produce picoliter droplets that form features on a surface as small as 30 μm wide. When combined with automatic surface height calibration, coefficients of variability for deposited feature diameters as small as 10% can be achieved. A wide range of fluids can be used, including aqueous solutions and many organic-solvent-based mixtures. Fluids that other dispensers struggle with, such as saturated solutions for MALDI-ToF matrices, or fluids with viscosities up to 450 cP, such as nano-particle suspensions or conductive inks, can be deposited with ease. The ultrasonic pumping action is also an efficient cleaning mechanism for quickly depositing many solutions sequentially.

In addition to spots, the Microplotter[®] Proto can draw true continuous features, such as lines, arcs, and bends. These are uniform elements, not made from overlapping droplets like other technologies, and are particularly well-suited to the polymer

Technical Specifications

Feature size	30 μm - 200 μm
Feature types	Droplets and contiguous lines
Deposition volume	≥ 1.8 pL
Deposition variability	As low as 10%
Viscosity	≤ 450 cP
Positioning	31 x 31 x 7 cm (X, Y, Z axes) 20 μm resolution
Calibration	Automatic surface height calibration
Camera	Digital video capture & recording
Computer	Included iMac
Software	SonoGuide control & SonoDraw CAD tools included
Dimensions	58.4 x 59.7 x 61 cm (23 x 23.5 x 24 in.)
Weight	TBA
Power	3.0 A for 100-120 V or 1.5 A for 220-240 V